

**TELEMETRY MODULE WITH CONFIGURABLE DATA
LAYER FOR USE WITH AN IMPLANTABLE MEDICAL DEVICE**

RELATED APPLICATION

- [01] This disclosure is related to the following co-pending application entitled "Telemetry Module With Configurable Physical Layer For Use With An Implantable Medical Device" by Goetz (U.S. Patent Application Serial No. _____; filed March 15, 2002) (Atty Docket No.: 011738.00057), which is not admitted as prior art with respect to the present disclosure by its mention in this section.

FIELD OF THE INVENTION

- [02] The present invention generally relates to implantable medical devices. More particularly, the invention relates to configuration of a telemetry unit for transmitting data to and from an implantable medical device.

BACKGROUND OF THE INVENTION

- [03] The medical device industry produces a wide variety of electronic and mechanical devices suitable for use outside and inside the body for treating patient disease conditions. Devices used outside the body are termed external while devices used inside the body are termed implantable medical devices and include devices such as neurostimulators, drug delivery devices, pacemakers, defibrillators, and cochlear implants. Clinicians use implantable medical devices alone or in combination with therapeutic substance therapies and surgery to treat patient medical conditions. For some medical conditions, implantable medical devices provide the best, and sometimes the only, therapy to restore an individual to a more healthful condition and a fuller life.
- [04] Implantable medical devices can be used to treat any number of conditions such as pain, cancer, incontinence, movement disorders such as epilepsy, spasticity, and Parkinson's disease, and sleep apnea. Additionally, use of implantable medical devices appears promising to treat a variety of physiological, psychological, and emotional conditions.

- [05] Implantable medical devices have important advantages over other forms of therapeutic substance administration. For example, oral administration is often not workable because the systemic dose of the substance needed to achieve the therapeutic dose at the target sight may be too large for the patient to tolerate without very adverse side effects. Also, some substances simply will not be absorbed in the gut adequately for a therapeutic dose to reach the target sight. Moreover, substances that are not lipid soluble may not cross the blood-brain barrier adequately if needed in the brain. In addition, infusion of substances from outside the body requires a transcutaneous catheter, which results in other risks such as infection or catheter dislodgement. Further, implantable medical devices avoid the problem of patient noncompliance, namely the patient failing to take the prescribed drug or therapy as instructed.
- [06] For example, one type of medical device is an Implantable Neuro Stimulator (INS). The INS is implanted at a predetermined location in the patient's body. The INS generates and delivers electrical stimulation signals at neurostimulation sites or areas to influence desired neural tissue, tissue areas, nervous system and organs to treat the ailment of concern. The stimulation sites can also include the spinal cord, brain, body muscles, peripheral nerves or any other site selected by a physician. For example, in the case of pain, electrical impulses may be directed to cover the specific sites where the patient is feeling pain. Neurostimulation can give patients effective pain relief and can reduce or eliminate the need for repeat surgeries and the need for pain medications.
- [07] Implantable medical devices are often used in conjunction with various computer and telecommunication systems and components. Information obtained by the implantable medical device may be stored and subsequently transmitted to a physician or patient caregiver or a database on demand or automatically. Many ways of using the information are known including decision making to provide optimum medical care to the person with the medical condition.
- [08] For example, an external device such as a physician programmer can be used to allow a physician to communicate with the implanted medical device. The physician programmer allows the physician to create and store stimulation therapy programs for the patient to be

delivered by the implanted medical device. The physician programmers also serve to recharge a rechargeable power source in the implanted medical device.

[09] Typically, the physician programmer communicates bi-directionally with the implanted medical device via RF telemetry signals. The bi-directional communication between the medical device and the physician or patient programmer is typically accomplished via a telemetry module. The physician programmer, the patient programmer and the medical device each have respective telemetry modules that allow for bi-directional communication between the medical device and the programmers. The bi-directional telemetry communication, between the medical device and the physician or patient programmers is typically conducted at frequencies in a range from about 150 KHz to 200 KHz using existing telemetry protocols. A telemetry protocol is generally an agreed-upon format for transmitting data between two devices. The protocol can be implemented in hardware and/or software. The protocol determines, for example, the type of error checking to be used, the data compression method, if any, how the sending device will indicate that it has finished sending a message, how the receiving device will indicate that it has received a message, etc. There are a variety of protocols, each having particular advantages and disadvantages; for example, some are simpler than others, some are more reliable, and some are faster. Ultimately, the external device must support the right protocol(s) in order to communicate with implanted device.

[10] Commercially available systems, however, are limiting in that the physician programmer is configured to provide telemetric communication using one or more pre-specified communication protocols. Accordingly, the physician programmer is typically only capable of communicating with those implanted medical devices that utilize those protocols. For each of the varying types of implanted devices available, the physician would need to have separate physician programmers that were compatible with each of the devices. Similarly, if the patient had more than one implanted device, the physician would likely need more than one physician programmer, one for each implanted device.

[11] It is therefore desirable to provide a physician programmer that may be operated using any number of protocol schemes so that it may communicate with any number of implanted devices.

BRIEF SUMMARY OF THE INVENTION

- [12] In general, the present invention provides a method and apparatus for communicating via telemetry with an implanted medical device. A telemetry module is provided that can be configured with a protocol driver that allows communication with the implanted device. In a first embodiment of the present invention, an implantable medical device system is disclosed having a programming device, a telemetry module, and an implanted medical device. The physician programmer launches an application that requires some level of interaction with an implanted medical device and that is specific to the implanted medical device. Upon launching of the application, the physician programmer configures a data layer of the telemetry module to enable communication of the implanted device. In particular, the programmer installs an appropriate protocol driver within the telemetry module that is compatible with the implanted medical device. The telemetry module, once configured with the appropriate protocol driver, may then facilitate communication between the implanted device and the physician programmer. For example, at least initially, the implanted device can provide to the physician programmer various configuration parameters of the implanted device.
- [13] In other embodiments, the telemetry module may be physically resident within the physician programmer. Alternatively, the telemetry module may operate to interact with a patient programmer or any other general-purpose computing device such as a personal computer or a hand-held Personal Digital Assistant (PDA) device, thereby allowing any such device to communicate with the implanted medical device.

BRIEF DESCRIPTION OF THE DRAWINGS

- [14] These and other advantages and features of the invention will become apparent upon reading the following detailed description and referring to the accompanying drawings in which like numbers refer to like parts throughout and in which:
- [15] Figure 1 is a schematic diagram of an exemplary implantable medical device system for use with the present invention.

- [16] Figure 2 depicts various views of a physician programmer in accordance with a preferred embodiment of the present invention.
- [17] Figure 3 depicts further various views of a physician programmer including the telemetry head in accordance with a preferred embodiment of the present invention.
- [18] Figure 4 is a schematic block diagram of an exemplary physician programmer for use with the present invention.
- [19] Figure 5 is a schematic block diagram of an exemplary implantable neurostimulator for use with the present invention.
- [20] Figure 6 is a schematic block diagram of a telemetry module in accordance with a preferred embodiment of the present invention.
- [21] Figure 7 is a schematic block diagram depicting the various software and hardware components of a telemetry module in accordance with a preferred embodiment of the present invention.
- [22] Figure 8 is a schematic block diagram depicting the software layers for handling communications between a physician programmer, a telemetry module, and an implantable medical device in accordance with a preferred embodiment of the present invention.
- [23] Figures 9-10 are flow charts illustrating the processes for configuring a telemetry module to enable communications with an implantable medical device in accordance with a preferred embodiment of the present invention.
- [24] Figure 11 is another flow chart illustrating the processes for configuring a telemetry module to enable communications with an implantable medical device in accordance with another preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

- [25] The present invention provides techniques for configuring a data layer of a telemetry module for communication with an implantable medical device. Although the present invention is described herein in conjunction with a neurostimulation system, those skilled in

the art will appreciate that the present invention may be implemented to communicate within any number of implantable medical devices including, but not limited to, implantable drug delivery devices, pacemakers, defibrillators, and cochlear implants. In fact, one aspect of the present invention enables the external device to be a universal device that can communicate with any number of implanted devices.

[26] Although not required, the invention will be described in the general context of computer-executable instructions, such as program modules. Generally, program modules include routines, programs, objects, scripts, components, data structures, etc. that perform particular tasks or implement particular abstract data types.

[27] Overview of an Implantable Medical Device System – Figure 1 shows the general environment of an implantable medical device system in accordance with a preferred embodiment of the present invention. The implantable medical device system generally includes an implantable medical device 5, such as an Implantable Neuro Stimulator (INS), a lead 11A, a lead extension 12A, a physician programmer 30, and a telemetry module 31. The system also typically includes other components, such as a patient programmer, an external therapy delivery device, and optionally various sensors, which are not shown. U.S. Patent Application Serial No. 10/002,328 entitled “Method and Apparatus for Programming an Implantable Device” filed on November 1, 2001, which is incorporated herein by reference in its entirety, discloses one example of an implantable medical device system for use with the present invention.

[28] Referring still to Figure 1, the implantable medical device 5 is implanted in the body in a subcutaneous pocket at a site selected after considering physician and patient preferences, typically near the abdomen of the patient. In the case where the implantable medical device 5 is an INS, the device is a modified implantable pulse generator that will be available from Medtronic, Inc. with provisions for multiple pulses occurring either simultaneously or with one pulse shifted in time with respect to the other, and having independently varying amplitudes and pulse widths. The INS 5 contains a power source and other electronics to send precise, electrical pulses to the spinal cord, brain, or neural tissue to provide the desired treatment therapy.

- [29] The lead 11A is a small medical wire with special insulation. The lead 11A includes one or more insulated electrical conductors with a connector on the proximal end and electrical contacts on the distal end. Some leads are designed to be inserted into a patient percutaneously, such as the Model 3487A Pisces-Quad® lead available from Medtronic, Inc. of Minneapolis Minnesota, and some leads are designed to be surgically implanted, such as the Model 3998 Specify® lead also available from Medtronic. The lead 11A may also be a paddle having a plurality of electrodes including, for example, a Medtronic paddle having model number 3587A. Alternatively, the lead 11A may provide electrical stimulation as well as drug infusion. Those skilled in the art will appreciate that any variety of leads may be used to practice the present invention depending upon the type of implantable medical device being used.
- [30] The lead 11A is implanted and positioned to provide treatment therapy to a specific site in the spinal cord or the brain. Alternatively, the lead 11A may be positioned along a peripheral nerve or adjacent neural tissue ganglia like the sympathetic chain or it may be positioned to provide treatment therapy to muscle tissue. In the case where electrical stimulation is to be provided, the lead 11A contains one or more electrodes (small electrical contacts) at a distal end 13A through which electrical stimulation is delivered from the implantable medical device 5 to the targeted neural tissue. If the spinal cord is to be stimulated, the lead 11A may have electrodes that are epidural, intrathecal or placed into the spinal cord itself. Effective spinal cord stimulation may be achieved by any of these lead placements.
- [31] The physician programmer 30, also known as a host programmer, uses a telemetry module (discussed further herein) to communicate with the implantable medical device 5, so a physician can program and manage a patient's therapy stored in the implantable medical device 5 and troubleshoot the implantable medical device system. An example of a physician programmer 30 is a Model 8840 Console Programmer soon to become available from Medtronic.
- [32] Figure 2 depicts views of the physician programmer 30 including a front view 203, a top view 207, a bottom view 208, a back view 205, a left side view 202, and a right side view 204. The physician programmer 30 is preferably a portable computing device having a user

interface. The user interface preferably includes a screen display 201 that is touch-sensitive to a pointing device 206 (Figure 3), similar to that of Personal Digital Assistants (PDA) available today. On the dorsal side 217 of the physician programmer 30 is an area to receive and hold the telemetry module 240. Figure 3 illustrates how the telemetry module 240 is insertable within a dorsal side 217 of the physician programmer 30. Figure 4 depicts the general componentry of the physician programmer 30, which includes a user interface 405, a processor 410, a transmitter, and a receiver. The application program software for handling the functionality of the programmer 30 discussed herein may be stored in memory 425.

[33] The physician programmer 30 acts as the control interface to the implanted medical device 5, which is generally dictated by the computer software application in the physician programmer. The software application generally has the following methods for implementing its control functionality: navigation methods; reporting methods; printing methods; data storage and transfer methods; data entry methods; methods to perform interrogation/review; methods to perform batch programming; user preferences; help methods; methods to resolve conflicts, and the like.

[34] As expressed previously, the present invention may be implemented generally for use with any number of implantable medical device systems including, but not limited to, implantable drug delivery devices, pacemakers, defibrillators, and cochlear implants. In the embodiment where the implanted medical device is an INS, Figure 5 provides a schematic block diagram of an exemplary INS 5. The INS generally includes a processor 540A with an oscillator 535A, a calendar clock 530A, memory 545A, and system reset 550A, a telemetry module 505A, a recharge module 510, a power source 515A, a power management module 520A, a therapy module 555A, and a therapy measurement module 560. Other components of the INS 5 can include, for example, a diagnostics module (not shown). All components except the power source 515A can be configured on one or more Application Specific Integrated Circuits (ASICs), may be part of one or more discrete components, or a combination of both. Also, all components except the oscillator 535A, the calendar clock 530A, and the power source 515A are connected to bi-directional data bus 525 that is non-multiplexed with separate address and data lines.

- [35] The processor 540A is synchronous and operates on low energy such as a Motorola 68HC11 synthesized core operating with a compatible instruction set. The oscillator 535A operates at a frequency compatible with the processor 540A, associated components, and energy constraints such as in the range from 100 KHz to 1.0 MHz. The calendar clock 530A counts the number of seconds since a fixed date for date/time stamping of events and for therapy control such as circadian rhythm linked therapies. The memory 545A includes memory sufficient for operation of the INS 5 such as volatile Random Access Memory (RAM) for example Static RAM, nonvolatile Read Only Memory (ROM), Electrically Erasable Programmable Read Only Memory (EEPROM) for example Flash EEPROM, and register arrays configured on ASICs. Direct Memory Access (DMA) is available to selected modules such as the telemetry module 505A, so the telemetry module 505A can request control of the data bus 525 and write data directly to memory 545A bypassing the processor 540A. The system reset 550A controls operation of ASICs and modules during power-up of the INS 5, so ASICs and modules registers can be loaded and brought on-line in a stable condition.
- [36] All component of the INS 5 are contained within or carried on a housing that is hermetically sealed and manufactured from a biocompatible material such as titanium. Feedthroughs provide electrical connectivity through the housing while maintaining a hermetic seal, and the feedthroughs can be filtered to reduce incoming noise from sources such as cell phones. Those skilled in the art will appreciate that the INS 5 may be configured in a variety of versions by removing modules not necessary for the particular configuration and by adding additional components or modules.
- [37] Overview of the Telemetry Module – Referring back to Figure 3, the telemetry module 240 is a relatively small device used to conveniently provide communication between the physician programmer 30 and the implanted medical device 5. The telemetry module 240 includes a programming head designed to support multiple existing and future implantable medical devices. The telemetry module 240 communicates directly with the implanted medical device via a modulated inductive link and with a host programming instrument (e.g., a physician programmer), preferably by means of a cable, but may be any sort of connection including, for example without limitation, RF and infrared.

- [38] Although in the preferred embodiment discussed herein the telemetry module 240 interacts with the physician programmer 30 as a separate device, those skilled in the art will appreciate that other embodiments are conceivable and still considered within the scope of the present invention. For example, the telemetry module 240 may be physically resident within the physician programmer 30 or any other programming device for use with an implantable medical device. Alternatively, the telemetry module 240 may operate to interact with a patient programmer or any other general-purpose computing device such as a personal computer or a hand-held Personal Digital Assistant (PDA) device, thereby allowing any such device to communicate with the implanted medical device 5.
- [39] FIGURE 6 is a schematic block diagram depicting the various components of the telemetry module 240 in accordance with a preferred embodiment of the present invention. The telemetry module 240 generally includes a host interface 605 (e.g., an interface to a physician programmer), a microcontroller 610, a power management module 615, a source of power 620, telemetry hardware, memory, and uplink and downlink interfaces to the implanted medical device. In this embodiment, the telemetry module 240 is a microprocessor-based device that includes software to control its functionality. Those skilled in the art will appreciate that the present invention may also be implemented using discrete logic-based or other circuitry.
- [40] The host interface 605 is preferably an asynchronous, full duplex serial port. The host interface 605, attaches directly to the telemetry module head itself and provides both power and a serial interface for messages and commands to and from the host 603. The source of power 620 is preferably provided by the host 603 having a voltage range of 4.0 and 12.0 volts, with 8.8 volts for optimal telemetry downlink power and 3.3 volts for use by the digital sections of the telemetry module 240. Those skilled in the art will appreciate that the telemetry module 240 may be powered in any number of ways including power supplied by the host and/or an internal power source (e.g., one or more batteries) in the telemetry module 240 itself. A regulator (not shown) supplies power to the analog receiver portions of telemetry module 240.
- [41] The memory 625 preferably includes FLASH memory as well as RAM memory. The FLASH memory may store platform firmware as well as up to nine protocol drivers

(discussed herein). Of course, with more memory or with smaller drivers, the number of stored protocol drivers could be arbitrarily larger (or smaller). One or more 64K byte sectors may be used for protocol driver execution or to store factory information, such as device serial number. The FLASH is connected to allow in-circuit programming, allowing both the platform code for the telemetry module 240, or individual protocol drivers to be saved or upgraded in its memory. An internal 4K RAM space is provided primarily for storage of STACK and possibly some critical global variables. An external SRAM may also be provided, which shares an address and data bus with the FLASH memory.

[42] Figure 7 is a schematic block diagram of the hardware and software components of the telemetry module 240 in accordance with a preferred embodiment of the present invention. Resident within memory 625 is software, which is subdivided into functions that are common across all uses of the telemetry module 240 (called the platform software 715) and functions that are specific to a particular protocol (called a protocol driver 725). The platform aspect of the telemetry module software is permanently resident within the telemetry module hardware itself. These components (platform software 715, the platform hardware 710, and the protocol driver interface 720) comprise the telemetry module platform that then host one or more installable protocol drivers 725. The protocol driver 725 is generally a program that acts as a translator between the implanted device and application programs 604 that use the device. Each implanted device has its own set of specialized commands that only its driver knows. In contrast, most programs access devices by using generic commands. The protocol driver 725, therefore, accepts generic commands from a program and then translates them into specialized commands that are understood by the implanted device.

[43] The platform software 715 controls the basic features of the platform hardware 710 and interfaces with the host 603 and the telemetry transceiver. For example, the platform software 715 handles initial boot procedure and initializations, manages the operational modes of the telemetry module 240, and manages the installation and subsequent launching of the protocol driver software. To support the operation of protocol driver software, the platform software 715 operates with the protocol driver interface 720, which provides a standardized interface that abstracts and encapsulates all of the functionality necessary for the protocol driver operations.

- [44] The platform software 715 functions are implemented across several distinct subsystems including, but not limited to, a host interface 730, a telemetry module executive 735, a block of utility functions 740, and a telemetry engine 745. The host interface 730 manages the serial channel communications with the host programming instrument. The host interface 730 includes a serial driver 733, a host protocol 732, and a message handler 731. The message handler 731 serves to process the various messages that can be received over the host interface 730 and routes them appropriately. In particular, the message handler 731 manages the serial driver 733, identifies the intended source and the validity of received messages, routes messages not intended for the basic telemetry module platform (e.g., test and protocol driver messages), responds appropriately to all other messages with either an acknowledgement of proper reception and routing, or with the expected data, and intercepts and acts on special message commands to facilitate non-standard features that exist outside the normal message protocol (e.g., reset command, override commands, etc.).
- [45] The telemetry module executive 735 handles basic operational modes of the telemetry module 240 and some of the built-in functions of the telemetry module 240 including, for example, the installation procedures for protocol driver 725, protocol driver verification and launching procedures, and test mode management facilities. For these exemplary functions, the telemetry module executive 735 includes a protocol driver installation manager 736, a telemetry module mode management module 737, and a test management module 738, respectively. The block of utility functions 740 include a self-test operations module 741, flash erasing and writing tools (in flash programming module 742), general purpose algorithms 743 (e.g., Cyclic Redundancy Check (CRC), checksum, etc.), and provisions for the other resources that are provided to the protocol driver 725 (e.g., timers, revision and ID information, etc.). The telemetry engine 745 holds a transmit driver 746 and a receive driver 747 and other primitive operations for the generation of and reception of telemetry waveforms.
- [46] The overall system includes a three-layer protocol stack that adds robustness to the serial channel physical layer. Figure 8 provides an illustration of the protocol layers of the telemetry module 240. Above the physical layer 805 are a data layer 810 and then a platform layer 815. The platform layer 815 is where messages are formed and sent, and where responses are received and processed. The data layer 810 is where the physical

integrity (framing, CRC checking, etc.) of all received information is accomplished. Platform Layer Messages (PLM) are passed to the data layer 810, which manages the actual transmission of the message. To accomplish this, the data layer 810 adds two items to the PLM; a header containing frame type and size information, and a CRC trailer used for validation. The completed product is called a "frame." There are three frame types. Messages to or from the Platform layer are frame type "DATA". The "ACK" and "NAK" frame types are assigned to messages that originate within the Data Layer, and are used to validate the transmission of "DATA" frames. A completed FRAME is buffered in the data layer 810 (in case of the need for re-transmission), and then sent through the physical layer 805 for actual transmission. One example for configuring the physical layer is disclosed in co-pending application entitled "Telemetry Module With Configurable Physical Layer For Use With An Implantable Medical Device" by Goetz (U.S. Patent Application Serial No. _____; filed March 15, 2002) (Atty Docket No.: 011738.00057), which is incorporated herein by reference. As discussed herein and in accordance with a preferred embodiment of the present invention, the data layer 810 may be configured by the application software with an appropriate protocol driver to operate in accordance with a desired telemetry protocol.

- [47] Those skilled in the art will appreciate that the telemetry module 240 may contain other hardware/software structures and still be able to incorporate the features of the present invention. In addition, those skilled in the art will appreciate that there may be any number of varying connections to the host 603 (e.g., from a cable to some form of wireless connection).
- [48] Figure 9 illustrates a flow chart illustrating the process for configuring a telemetry module 240 by the application software 604. The host 603 (e.g., physician programmer) includes a base module platform software 606 that manages the various procedures for configuring the telemetry module 240. The base module platform software 606 generally includes mechanisms for identifying the desired protocol driver 725 from among several saved on a card or in memory, checking the integrity of the protocol driver 725, communicating with the telemetry module 240 to initiate the transfer, transferring the binary data that comprises the protocol driver 725, and verifying the integrity of the transfer. The telemetry module 240 includes an operating system that performs secondary operations for protocol installation, including, for example, loading the protocol driver 725 into memory.

- [49] Referring still to Figure 9, at step 905, the host device 603 (e.g., physician programmer) is turned on and, at step 910, the host 603 launches in response to user input an application program 604. The application program 604 and corresponding protocol driver 725 may be stored in a memory such as compact flash card. The application program 604 preferably includes, as part of its file structure, a file containing the protocol driver 725 that it uses for its telemetric communications. As part of its startup activities, the application program 604 points the base module platform software 606 to this file. The application program 604 then instructs the base module platform software 606 to have the protocol driver 725 installed.
- [50] At step 915, the base module platform software 606 opens the protocol driver file and loads it into memory. At step 920, the host 603 confirms whether the protocol driver 725 is loaded. If it has not loaded, at step 930, the host 603 signals the user that the driver has not loaded (typically, due to a corrupt flash card) and, at step 940, halts further operation. If the protocol driver 725 has loaded, at step 925, the host 603 verifies that the protocol driver 725 is a valid. If loading of the protocol driver 725 is not valid, at step 930, the host 603 signals the user that the driver has not loaded and, at step 940, halts further operation. If the loading of the protocol driver 725 is valid, at step 945, the host 603 installs the protocol driver 725 in the telemetry module 240.
- [51] At step 950, the protocol driver 725 is installed in the telemetry module 240. This procedure is described in further detail herein. At step 955, the installation process continues until it is complete and, at step 960, the host 603 may perform certain checks to determine whether the installation was successful. If the installation was successful, the telemetry module 240 is ready to initiate communication and, at step 970, queries the implanted device for its communications capabilities and, at step 980, determines whether the telemetry module 240 requires further configuration. If no further configuration is necessary, which is likely to be the case for most existing implanted devices, the telemetry module 240 is ready to begin telemetric communication, at step 990. If further configuration is necessary, at step 985, the telemetry module 240 configures the hardware and software in the implanted device and the telemetry module 240 for optimal operation. Configuration parameters may include, for example, data rate, telemetry scheme, etc. As discussed, one example for configuring the physical layer of the telemetry module 240 is disclosed in co-pending application entitled "Telemetry Module With Configurable Physical

Layer For Use With An Implantable Medical Device" by Goetz (U.S. Patent Application Serial No. _____; filed March 15, 2002) (Atty Docket No.: 011738.00057)

[52] Figure 10 is a flow chart providing a more detailed description of the installation of the protocol driver 725 procedure, including steps 950 and subsequent steps. At step 1005, the base platform module of the host 603 parses the protocol driver 725 and, at step 1010, extracts the identification number and revision number of the protocol driver 725. Each protocol driver 725 preferably has a unique identification number and a revision number to provide information regarding any possible updates to the protocol driver 725. At step 1015, the host 603 initializes the telemetry module 240 to ensure that it is operating properly. At step 1020, the host 603 queries the telemetry module 240 for installed protocol drivers 725, particularly the identification number and revision number of each installed protocol driver 725. At step 1025, the host 603 checks whether the protocol driver 725 to be installed is already installed in the telemetry module 240. If it is, then there is no need to reinstall the protocol driver 725 and, at step 1030, the telemetry module 240 is instructed to launch the desired protocol driver 725. At step 1035, the telemetry module 240 signals the application 604 in the host 603 that the telemetry module 240 is successfully configured for communication with the implanted device and, at step 1060, launches the protocol driver 725.

[53] If the desired protocol driver 725 is not already installed, then further processing is necessary to proceed with the installation. At step 1040, the telemetry module memory is checked to see if it is full. For example, the telemetry module 240 may be capable of storing a maximum of nine protocol drivers 725. If the telemetry module memory is not full, at step 1050, the host 603, in concert with the telemetry module operating system, installs the desired protocol driver 725 into the telemetry module 240. If the telemetry module memory is full, at step 1045, the host 603 randomly selects protocol driver 725 in the telemetry module memory, and at step 1055, uninstalls the randomly selected protocol driver 725. At step 1050, the host 603, in concert with the telemetry module operating system, installs the desired protocol driver 725 into the telemetry module 240.

- [54] At step 1065, the telemetry module 240 confirms whether the installation was successful. If yes, at step 1060, the telemetry module 240 launches the protocol driver 725. If no, the telemetry module 240 signals the host 603 that the telemetry module configuration failed.
- [55] Advantageously, the telemetry module 240 may be upgraded, for example by installing hardware or software to enable faster telemetry, without requiring replacement of the physician programmer.
- [56] In accordance with another embodiment of the present invention, the telemetry head may be dynamically configured to simultaneously support various configurations of any chosen telemetry protocol. For example, a telemetry protocol may be further configured to enable optimal communication efficiency and data integrity. For example, U.S. Patent Application Serial Number 09/665,874, entitled "Telemetry Modulation Protocol System For Medical Devices" and filed on September 20, 2000, which is incorporated herein by reference in its entirety, discloses one such telemetry scheme that can be further configured. Figure 11 is a flow chart illustrating the process for dynamically configuring a telemetry module 240. At step 1105, the host 603 is turned on, which launches an application program 604 corresponding to the implanted medical device. At step 1110, the host 603 queries the telemetry module platform for its capabilities. For examples, the telemetry module platform may provide information such as its parameter, parameter ranges, parameter resolutions, etc. At step 1115, the host 603 checks whether the telemetry module 240 can support the desired protocol. If no, at step 1120, the host 603 signals the user that the telemetry module 240 is incapable of supporting the desired telemetry protocol. If yes, at steps 1125 through 1150, the telemetry module 240 is prepared for telemetry communication in accordance with the procedures described above.
- [57] Although described for use with a physician programmer, the telemetry module 240 of the present invention may also be implemented for use with host devices other than the physician programmer including, but not limited to, a general purpose computing device such as a personal computer, a laptop or a hand-held device, or a cellular device.
- [58] Those skilled in that art will recognize that the preferred embodiments may be altered or amended without departing from the true spirit and scope of the invention, as defined in the

accompanying claims. Thus, while various alterations and permutations of the invention are possible, the invention is to be limited only by the following claims and equivalents.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230